

ELEGANZA® Spray Equipment

Recommended supplier and specifications to spray Eleganza® Silent Plaster

KNAUFCEILING
Solutions

Machine Specifications

For an ideal spray pattern with the highest absorbing efficiency, the following parameters must be urgently considered when selecting the delivery pump and the compressor.

Spray pump

- Rotor speed infinitely adjustable from 0 l/min
- Pointed spray gun with 4mm nozzle (not all these models work)

Compressor

- 400 – 450 l/min (output not input)
- 10 bar pressures, when operating approx. 4 bar
- The pressure must be kept constant!

STROBL – Maschinenbau Rudolf

Company details

- small, owner-managed company
- machines are sold to a lot of countries

Contact

Homepage: www.rudolf-strobl.de

Telephone: +49 2486 802460

E-Mail: info@rudolf-strobl.de

Contact: Holger Metzler

+49 171 7457674

h.metzler@rudolf-strobl.de

Suitable Equipment: Example Strobl Eleganza® Setup

■ Setup 1 | Setup for STROBOT 401 RS 30



No.	Picture	Product	STROBL Item number
		Spray pump STROBOT 401 RS 30	111533036
		finish-coat spray set with GEKA couplings contains:	470459
1		Mortar hose NW 19, 15 m with 2 mortar couplings	470458
2		Airline, NW 9, 25 m	462721
3		Fine plaster spray unit, small with handgrip without nozzles	463859
6		Remote control cable with control lamp, 16.3 m	70350
		Nozzle, 4 mm / 32 mm small for 0,4 mm grain size	on request
		Stator EW 40, STROBOT 326/40X/507	63793
		Rotor FC 40, Stainless steel hard chrome-plated, slotted, STROBOT 326/40X/507	469737
		Compressor Strocomp 865 Airflow per minute: 550 l/min (1 bar) max. air pressure: 10 bar	111593012

+++ part of the finish coat set +++

Suitable Equipment: Example Strobl Eleganza® Setup

■ Setup 2 | Setup for STROBOT 305 RS



No.	Picture	Product	STROBL Item number
		Spray pump STROBOT 401 RS 30	111533036
		finish-coat spray set with GEKA couplings contains:	470459
1		Mortar hose NW 19, 15 m with 2 mortar couplings	470458
2		Airline, NW 9, 25 m	462721
3		Fine plaster spray unit, small with handgrip without nozzles	463859
6		Remote control cable with control lamp, 16.3 m	70350
		Nozzle, 4 mm / 32 mm small for 0,4 mm grain size	on request
		Stator MK 20 white	63793
		Rotor stainless steel FC 20	469737
		Compressor Strocomp 865 Airflow per minute: 550 l/min (1 bar) max. air pressure: 10 bar	111593012

+++ part of the finish coat set +++